

## Flow Measurement

### SITRANS FC (Coriolis)

#### Sensors and Flowmeter systems

#### MASS 2100 / FC300 DN 4 with FCT030 transmitter

##### Overview



Sensors MASS 2100 and FC300 DN 4 with FCT010 / FCT030 transmitters

The SITRANS MASS 2100 and FC300 DN 4 system consists of a SITRANS sensor and a SITRANS FCT030 transmitter.

The flowmeter comes in a compact and remote design depending for all MASS 2100 DI 3 to DI 15.

MASS 2100 DI 1.5 and FC300 DN4 are only available with analogue connection of the FCT030 transmitter.

The flowmeter is based on the latest developments within digital signal processing technology – engineered for high measuring performance:

- Fast response to rapid changes in flow
- Fast dosing applications
- High immunity against process noise
- High turndown ratio of flowrates
- Suitable for liquid and gas service
- Easy to install, commission and maintain

FCT030 is available with current output HART 7.5, Modbus RS 485 RTU, PROFIBUS DP or PROFIBUS PA as standard on Channel 1. Additional functions can be freely configured for analog, pulse, frequency, relay or status output or binary input.

The transmitter comes with a user-configurable graphical display and SensorFlash, a microSD card for configuration backup, firmware update and data storage.

##### Benefits

- High accuracy better than 0.1 % of mass flow rate
- Large dynamic turn-down ratio better than 500:1
- Densitometer performance available through density accuracy (depending upon sensor size) ranging from 0.0005 to 0.0015 g/cm<sup>3</sup> with a typical repeatability better than 0.0001 to 0.0002 g/cm<sup>3</sup>
- Single continuous tube design, with no internal welds, reductions or flow splitters offers optimal hygiene, safety and CIP cleanability for food and beverage and pharmaceutical applications
- Markets biggest wall thickness, ensuring optimal life-time and corrosion resistance and high-pressure durability
- Balanced pipe design with little mechanical energy-loss, ensures optimal performance and stability under non-ideal and unstable process conditions (pressure, temperature, density-changes etc.)
- Full bore design provides lower pressure loss due to same internal diameter throughout the entire sensor
- 4-wire Pt1000 temperature measurement ensures optimum accuracy on mass flow, density and fraction flow
- Multi-plug electrical connector enables true “plug & play”
- Sensor pipe available in high-quality stainless steel AISI 316L/1.4435 or Hastelloy C22/2.4602 offering optimum corrosion resistance
- Centre-block design decouples process noise from the environment such as vibrations, pulsations, pressure shocks etc. making installation flexible and versatile
- Rugged and space-saving sensor design in stainless steel matching all environments
- High-pressure program as standard

### Technical specifications

Sensors MASS 2100 / FC300 DN 4 with FCT030 transmitter	
<b>Sizes mm ( inch)</b>	MASS 2100 DI 1.5 (1/16) MASS 2100 DI 3 (1/8") MASS 2100 DI 6 (1/4") MASS 2100 DI 15 (1/2") FC300 DN 4 (1/6")
<b>Accuracy</b>	± 0.10 % for liquids additional ±0.40 for gases
<b>Repeatability</b>	± 0.05 %
<b>Flow range Q norm (liquids)</b> (water @ 1 bar pressure loss) (Q <sub>nom</sub> )	
• DI 1.5	19 kg/h (42 lb/h)
• DI 3	90 kg/h (198 lb/h)
• DI 6	500 kg/h (1 102 lb/h)
• DI 15	3 800 kg/h (8 370 lb/h)
• DN 4	140 kg/h (308 lb/h)
<b>Architecture</b>	Compact: DI 3, DI 6, DI 15 Remote digital: DI 3, DI 6, DI 15 Remote analogue: DI 1.5, DI 3, DI 6, DI 15, DN 4
Display	Full graphical display, 240 × 160 pixels with selection of 6 languages
Power supply	20 ... 90 V DC ± 10 %; 100 ... 240 V AC ± 10 %, 47 ... 63 Hz ± 10 %
<b>Material</b>	
• Sensor	
- Wetted parts	316L stainless steel or Hastelloy C 22
- Enclosure	316L stainless steel
• Transmitter	Aluminum with corrosion-resistant coating Class C4
<b>Enclosure rating</b>	IP67 <sup>1)</sup>
<b>Pressure ratings</b>	
• Measuring tubes	
- 316L	Up to 265 bar (3 844 psi), depending on size and process connection
- Nickel Alloy C4	Up to 410 bar (5 945 psi), depending on size and process connection
• Sensor enclosure	No pressure containment
Temperature ratings	
• Process medium	-50 ... +180 °C (-58 ... +356 °F)
• Ambient	-20 ... +50 °C (-4 ... +122 °F) <sup>1)</sup>

Sensors MASS 2100 / FC300 DN 4 with FCT030 transmitter	
<b>Process connections (depending on size and pressure rating)</b>	
• Flanges	EN 1092-1 B1, ANSI/ASME B16.5
• Pipe threads	ASME B1.20 (NPT), ISO 228
• Hygienic threads	DIN 11851, ISO 2853/BS 4825 part 4 (SS3016)
• Hygienic clamps	ISO Clamp 2852
<b>Approvals</b>	
• Hazardous area	ATEX, IECEx, EAC Ex, CSA, cCSAus, EAC PED
• Pressure equipment	
<b>NAMUR</b>	NAMUR-compliant (e.g. NE 21, NE 41, NE 107 and NE 132)
<b>I/O</b>	Up to 4 channels combining analog, relay or digital outputs and binary input
<b>Communication</b>	HART PROFIBUS PA PROFIBUS DP Modbus RTU (RS 485)
<b>EMC performance</b>	
• Emission	EN 55011/CISPR-11 (Class A)
• Immunity	EN/IEC 61326-1 (Industry)
<b>Mechanical load</b>	18 ... 1 000 Hz random The flow meter will mechanically tolerate 3.17 g RMS in all directions. Flow accuracy cannot be guaranteed under all conditions.

<sup>1)</sup> If operating outdoors, avoid direct sunlight, particularly in warm climatic regions.

## Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems

### MASS 2100 / FC300 DN 4 with FCT030 transmitter

#### Selection and ordering data

Article No.

Article No.

**SITRANS FC sensors MASS 2100/FC300 with FCT030 transmitter**

7ME4813-

Ord.  
code

Click on the Article No. for the online configuration in the PIA Life Cycle Portal.

#### Sensor type and connector size

MASS 2100 DI 1.5, 1/4"	1 G
MASS 2100 DI 3, 1/4"	3 A
MASS 2100 DI 3, 1/4" Heated w. DIN	3 B
MASS 2100 DI 3, 1/4" Heated w. ANSI	3 C
FC300 DN 4, 1/4"	4 A
MASS 2100 DI 6, 1/4"	6 A
MASS 2100 DI 6, 1/4" Heated w. EN	6 B
MASS 2100 DI 6, 1/4" Heated w. ANSI	6 C
MASS 2100 DI 6, DN 10	6 D
MASS 2100 DI 6, DN 10 Heated w. EN	6 E
MASS 2100 DI 6, DN 10 Heated w. ANSI	6 F
MASS 2100 DI 6, DN 15 (1/2")	6 G
MASS 2100 DI 6, DN 15 (1/2") Heated w. EN	6 H
MASS 2100 DI 6, DN 15 (1/2") Heated w. ANSI	6 J
MASS 2100 DI 6, DN 20 (3/4")	6 K
MASS 2100 DI 6, DN 20 (3/4") Heated w. EN	6 L
MASS 2100 DI 6, DN 20 (3/4") Heated w. ANSI	6 M
MASS 2100 DI 6, DN 25 (1")	6 N
MASS 2100 DI 6, DN 25 (1") Heated w. EN	6 P
MASS 2100 DI 6, DN 25 (1") Heated w. ANSI	6 Q
MASS 2100 DI 15, DN 15 (1/2")	7 A
MASS 2100 DI 15, DN 15 (1/2") Heated w. EN	7 B
MASS 2100 DI 15, DN 15 (1/2") Heated w. ANSI	7 C
MASS 2100 DI 15, DN 20 (3/4")	7 D
MASS 2100 DI 15, DN 20 (3/4") Heated w. EN	7 E
MASS 2100 DI 15, DN 20 (3/4") Heated w. ANSI	7 F
MASS 2100 DI 15, DN 25 (1")	7 G
MASS 2100 DI 15, DN 25 (1") Heated w. EN	7 H
MASS 2100 DI 15, DN 25 (1") Heated w. ANSI	7 J

**SITRANS FC sensors MASS 2100/FC300 with FCT030 transmitter**

7ME4813-

Ord.  
code

#### Process connection/Pressure

No connections (spare part transmitter)	A 0
EN 1092-1 B1, PN 40	A 1
EN 1092-1 B1, PN 100	A 3
ASME B16.5, RF, Class 150	D 1
ASME B16.5, RF, Class 600	D 3
DIN 11851 crewed connection	F 1
ISO 2852 hygienic clamped	J 1
ISO 2853 hygienic screwed	J 5
ISO 228-1 pipe thread, PN 100	C 1
ISO 228-1 pipe thread, PN 130	C 2
ISO 228-1 pipe thread, PN 200	C 3
ISO 228-1 pipe thread, PN 230	C 4
ISO 228-1 pipe thread, PN 265	C 5
ISO 228-1 pipe thread, PN 350	C 6
ISO 228-1 pipe thread, PN 365	C 7
ISO 228-1 pipe thread, PN 410	C 8
NPT ASME B 1.20.1 pipe thread, PN 100	N 1
NPT ASME B 1.20.1 pipe thread, PN 130	N 2
NPT ASME B 1.20.1 pipe thread, PN 200	N 3
NPT ASME B 1.20.1 pipe thread, PN 230	N 4
NPT ASME B 1.20.1 pipe thread, PN 265	N 5
NPT ASME B 1.20.1 pipe thread, PN 350	N 6
NPT ASME B 1.20.1 pipe thread, PN 365	N 7
NPT ASME B 1.20.1 pipe thread, PN 410	N 8

#### Tube material (wetted) and max. operational temperature

AISI 316L/EN 1.4435, max. 115 °C	1
AISI 316L/EN 1.4435, max. 125 °C	2
AISI 316L/EN 1.4435, max. 180 °C	3
Hastelloy C22/UNS N06022/EN 2.4602, max. 115 °C	5
Hastelloy C22/UNS N06022/EN 2.4602, max. 125 °C	6
Hastelloy C22/UNS N06022/EN 2.4602, max. 180 °C	7

#### Calibration

Mass flow calibration 2 flow x 2 points	1
Mass flow calibration 2 flow x 2 points + density calibration	4
Standard fraction (selectable by menu) incl density calibration	8
Individual fraction (on demand)	9

N O Y

Selection and ordering data	Article No.	Order code
<b>SITRANS FC sensors MASS 2100/FC300 with FCT030 transmitter</b>	<b>7ME4813-</b>	Ord. code
	-	
<b>Mounting style, transmitter housing and material</b>		
Compact mounted, IP67, Aluminium transmitter housing (DI 3, DI 6 and DI 15 )	<b>D</b>	
Remote field mounted, IP67, Aluminium housing, M12 socket for digital cable connection (DI 3, DI6 and DI 15 only)	<b>G</b>	
Remote field mount, IP67, Aluminium housing, terminal box for digital cable connection (DI 3, DI6 and DI 15)	<b>K</b>	
Wall mount aluminum transmitter housing, M12 socket for digital cable connection (DI 3, DI 6 and DI 15 )	<b>U</b>	
Remote field mount, IP67, Aluminium transmitter housing, analog cable connection with M20 connectors	<b>Z</b>	<b>P 0 D</b>
Remote wall mount, IP67, aluminum transmitter housing, analog cable connection with M20 connectors	<b>Z</b>	<b>P 0 E</b>
<b>Ex approvals</b>		
Non-Ex		
ATEX Zone 1 / 21		
IECEX Zone 1 / 21 (in preparation)	<b>A</b>	
USA (FM, CSA, UL), Zone 1/Div 1	<b>C</b>	
Canada (CSA, UL), Zone 1/Div 1	<b>F</b>	
EAC Zone 1 / 21	<b>H</b>	
	<b>M</b>	
	<b>U</b>	
<b>Local User Interface</b>		
Blind		<b>1</b>
Graphical, 240 × 160 pixels, glass lid		<b>3</b>
<b>Further designs</b>		
Please add "-Z" to Article No. and specify Order code(s).		
<b>Cable glands</b>		
None (mechanical sensor)		<b>A00</b>
Metric, no glands		<b>A01</b>
Metric, plastic		<b>A02</b>
Metric, brass/Ni plated		<b>A05</b>
Metric, stainless steel		<b>A06</b>
NPT, no glands		<b>A11</b>
NPT, plastic		<b>A12</b>
NPT, brass/Ni plated		<b>A15</b>
NPT, stainless steel		<b>A16</b>
Integral M12 socket		<b>A20</b>
<b>SW functions &amp; CT approvals</b>		
Standard		<b>B11</b>
<b>I/O configuration Ch1</b>		
None (replacement sensor)		<b>E00</b>
4 ... 20 mA, HART, active/passive output (non-Ex)		<b>E02</b>
4 ... 20 mA, HART, active Ex		<b>E06</b>
4 ... 20 mA, HART, passive Ex		<b>E07</b>
PROFIBUS PA		<b>E10</b>
PROFIBUS DP		<b>E11</b>
Modbus RTU RS 485 (none-Ex)		<b>E14</b>
<b>I/O configuration Ch2, Ch3 and Ch4</b>		
None		<b>F00</b>
Non Ex: Sig O, None, None		<b>F01</b>
Non Ex: Sig O, Sig I/O, None		<b>F02</b>
Non Ex: Sig O, Sig I/O, Sig I/O		<b>F03</b>
Non Ex: Sig O, Sig I/O, R		<b>F04</b>
Non Ex: Sig O, R, R		<b>F05</b>
Non Ex: Sig O, R, None		<b>F06</b>
Ex: pSig O, None, None		<b>F11</b>
Ex: pSig O, pSig I/O, None		<b>F12</b>
Ex: pSig O, pSig I/O, pSig I/O		<b>F13</b>
Ex: pSig O, pSig I/O, R		<b>F14</b>
Ex: pSig O, R, R		<b>F15</b>
Ex: pSig O, R, None		<b>F16</b>
Ex: aSig O, None, None		<b>F21</b>
Ex: aSig O, aSig I/O, None		<b>F22</b>
Ex: aSig O, aSig I/O, aSig I/O		<b>F23</b>
Ex: aSig O, aSig I/O, R		<b>F24</b>
Ex: aSig O, R, R		<b>F25</b>
Ex: aSig O, R, None		<b>F26</b>

## Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems

### MASS 2100 / FC300 DN 4 with FCT030 transmitter

3

#### Selection and ordering data

#### Order code

##### Further designs

Please add "-Z" to Article No. and specify Order code(s).

##### Certificates

Press test certificate CRN	C01
Press test certificate PED	C02
Material certificate EN 10204-3.1	C12
Welding inspection report	C13
Factory certificate according to EN 10204 2.2	C14
Factory certificate according to EN 10204 2.1	C15
Cleaning for oil and grease/ASTM-A380	C50

##### Sensor data storage

Sensor with SensorFlash for FCT	S20
Sensor with SensorProm for MASS 6000 (in preparation)	S21

##### SD-Card accessibility via USB

(not allowed in USA by Patent)

Mass storage enabled	S30
----------------------	-----

##### Digital cable sensor-transmitter

None	L50
5 m (16.4 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L51
5 m (16.4 ft), sensor cable, 4 wire, without plugs for terminal connection	L52
10 m (32.8 ft) sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L55
10 m (32.8 ft), sensor cable, 4 wire, without plugs for terminal connection	L56
25 m (82 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L59
25 m (82 ft), sensor cable, 4 wire, without plugs for terminal connection	L60
50 m (164 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L63
50 m (164 ft), sensor cable, 4 wire, without plugs for terminal connection	L64
75 m (246 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L67
75 m (246 ft), sensor cable, 4 wire, without plugs for terminal connection	L68

##### Analog cable sensor-transmitter

1 m cable, analog, with 2 × M20 connectors	L85
2 m cable, analog with 2 × M20 connectors	L86
5 m cable, analog with 2 × M20 connectors	L87
10 m cable, analog with 2 × M20 connectors	L88
15 m cable, analog with 2 × M20 connectors	L89

##### Additional data

Please add "-Z" to Article No. and specify Order code(s) and plain text.


##### Tag name

Tag name plate, stainless steel	Y17
---------------------------------	-----

##### Extended calibration

Multi-point high, (5 flows × 2 passes), 10 ... 100 % of $Q_{nom}$	Y61
Multi-point high, (10 flows × 1 pass), 10 ... 100 % of $Q_{nom}$	Y63

#### Accessories for MASS 2100 and FC300 DN 4 with FCT030 transmitter

Description	Article No.	
Mounting bracket for flow sensor MASS 2100 DI 1.5	A5E02590427	
Mounting bracket for FC300 DN 4 in AISI 304	A5E02590439	